



Product Specification and Technical Data

PRODUCT: **BG 244[®]**
Diesel Fuel System Cleaner

PART NO.: 244

TEST DATA:	Test	ASTM Test Method	Typical Test Results
	API Gravity @ 15.6°C (60°F)	D287	29.3
	Specific Gravity @ 15.6°C (60°F)	D1298	0.8802
	Density, U.S. lbs./gal. (kg/L) @ 15.6°C (60°F)	D1250	7.338
	Flash Point, PMCC	D93	53°C (127°F)
	Viscosity, cSt 40°C (104°F)	D445	4.3
	Pour Point	D97	<-40°C (-40°F)
	Color	D1500	2.0
	Color	Visual	Amber

PROBLEM: Diesels are extremely sensitive to fuel degradation. Fuel breakdown byproducts impede injection and increase deposit buildup, leading to heavy exhaust emissions and power loss.

SOLUTION: BG 244[®] Diesel Fuel System Cleaner dissolves and removes deposits from the entire diesel injection system, including fuel injectors and combustion chambers.

- Lubricates fuel pumps and injectors
- Contains cetane improver
- Complies with the federal low sulfur content requirements for use in diesel motor vehicles
- Catalytic converter, diesel particulate filter and oxygen sensor safe
- Contains no alcohol

- BENEFITS:**
- Improves cold start
 - Restores fuel economy
 - Reduces harmful emissions
 - Restores horsepower
 - Smooths idle
 - Protects fuel system

USAGE: Add BG 244[®] to vehicle fuel tank at fill-up. One 3 fl. oz. (100 mL) bottle treats 4–6 gallons (15–23 Liters) of diesel fuel. One 6 fl. oz. (177 mL) bottle treats 6-10 gallons (23-38 Liters) of diesel fuel. One 11 fl. oz. (325 mL) can treats 10–15 gallons (38–60 Liters) of diesel fuel. One quart (946 mL) treats up to 20–40 gallons (75–150 Liters) of diesel fuel. FOR PROFESSIONAL USE.

BG Products, Inc., accepts no liability for excessive use or misuse of this product.